



**TECHNICAL DATA SHEET**

<b>Order reference</b>	<b>SB-3</b>
<b>Article number</b>	<b>813921</b>

<b>Date</b>	10-05-2006	<b>Replaces</b>	New	<b>No. Pages</b>	1
-------------	------------	-----------------	-----	------------------	---

**Product Description:**

<b>Style</b>	Spill barrier length= 3m, h= 5.5 cm, w=10.5 cm
<b>Composition</b>	1 – triangle serpentine spill barrier, 100% polyurethane
<b>Color</b>	Yellow
<b>Absorbency</b>	N/A

<b>Intended Application</b>	Designed to contain or divert spills
-----------------------------	--------------------------------------

<b>Absorbency Capacity</b>	N/A
----------------------------	-----

**Packaging Description:**

Package configuration	1 Case	Pkg. Weight	10.8 kg
Items per Package	1 unit/Case	Pkg. Dimensions	61 x 41 x 21 cm
Container type	Carton		

**Physical Properties:**

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Color	Visual	-----	Yellow	per standard

**The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.**

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
<b>Certification</b>	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.