



TECHNICAL DATA SHEET

Order reference	SPCJR-1210
Article number	813805

Date	11-14-06	Replaces	New	No. Pages	1
-------------	----------	-----------------	-----	------------------	---

Product Description:

Style	Contractor Boom
Item Size (each)	15 cm Float, 30 cm Skirt, total length = 30 m, floatation length 1.8m
Composition	Vinyl coated Polyester PVC 745 g /m ²
Structure	Floatation material wrapped in cylindrical tubes with a Vinyl coated Polyester PVC fabric skirt hanging into the water held down by a tension member inside the bottom of the skirt to prevent under flow of oil.
Connections	Universal Aluminum or ASTM "Z" Type
Tension Member	6mm hot dip galvanized chain
Color	International Yellow
Cleaning	Industrial detergents, steam, pressure wash, etc.
Absorbency	No absorbency

Intended Application	Containment barrier of oil on water in rivers and harbors at a wave height of max 1 meter or wind speed of 28-37 km/hr
-----------------------------	--

Packaging Description:

Package configuration	Geotextile	Pkg. Weight	75 kg
Items per Package	1 Boom	Pkg. Dimensions	185 cm x 75 cm x 75 cm
Container type	Geotextile		

Physical Properties:

<u>Parameter</u>		<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Total tensile strength		daN	2273	
Temperature range		°C	-34°C to +64°C	
Color	Visual	-----	International Orange	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.