



TECHNICAL DATA SHEET

| | |
|------------------------|-------------------|
| Order reference | UN15-DPS-E |
| Article number | 813846 |

| | | | | | |
|-------------|---------|-----------------|----------|------------------|---|
| Date | 4-11-11 | Replaces | 03-31-08 | No. Pages | 1 |
|-------------|---------|-----------------|----------|------------------|---|

Product Description:

| | |
|-------------------------|--|
| Style | Economical Blanket Rolls; high strength perforation down the middle for the 19 cm wide dimension, & cross-wise for the 23cm long dimension. |
| Item Size (each) | 38 cm wide by 23 m long (100 pads per roll) |
| Color | Green |
| Composition | Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 % |
| Structure | 96% natural white meltblown nonwoven fibers(<10 microns) 4% white spunbond nonwoven coverstock(<15-30 microns) |
| Technology | Meltblown + spunbond |
| Absorbency | Universal (Hydrophilic + Oleophilic) |
| Bonding | Bonded (staggered pattern) + Mechanical entanglement |

| | |
|-----------------------------|--|
| Intended Application | Low -Lint Chemical & Static Resistant Sorbent for Water, Oil, or Solvent Base Liquids. |
|-----------------------------|--|

| | |
|----------------------------|---|
| Absorbency Capacity | 35 l per bale (saturated; medium viscosity-12.5x) |
|----------------------------|---|

Packaging Description:

| | | | |
|-----------------------|--------------------------|-----------------|-------------------------------|
| Package configuration | Case | Pkg. Weight | 3.7 kg (2.4 kg) |
| Items per Package | 1-Rolls/Case 100 pads | Pkg. Dimensions | 34.5 cm x 34.5 cm x44.5 cm |
| Container type | Carton dispenser box | | |

Physical Properties:

| <u>Parameter</u> | <u>SPC Test Method</u> | <u>Units</u> | <u>Nominal</u> | <u>(+/-)Tolerance</u> |
|-----------------------|------------------------|--------------|----------------|-----------------------|
| Basis Weight | SPCTM-002 | G/M2 | 295 | 29 |
| Caliper | SPCTM-020 | mm | 4.5 | 0.4 |
| Absorbency (med visc) | SPCTM-004B | gL/gS | 12.5 | 2 |
| Tensile Strength | SPCTM-007 | daN | 11.5 | 1.1 |
| Color | Visual | ----- | Green | per standard |

The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

| | |
|----------------------|--|
| Attributes | Product will be free of foreign material contamination, rips, holes, and tears. |
| Labeling | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code). |
| Certification | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |